

Tools

Design features


- First ensure that the grip ring is not under tension. When pushed in, the extractors separate the grip ring from the pipe, which can then be pulled out
- **Application:** for all Hawle products with ISO push-fit fittings

Order No.	Ø Pipe	DN	Qty. Extractors	Weight	
6010	20	1/2"	2	0,04	
	25	3/4"	2	0,07	
	32	1"	2	0,09	
	40	1 1/4"	2	0,14	
	50	1 1/2"	2	0,19	
	63	2"	2	0,36	
	75		3	0,18	
	90		3	0,31	
	110		3	0,41	

Extractors

For dismantling ISO push-fit fittings

No. 6010



Design features

- Made of aluminium and ductile iron with reversible ratchet
- For opening and closing
- For operating coupling caps A + B + C
- For operating hose couplings B + C
- For breaking theft indicator caps

Order No.	Weight	
3461	2,50	

Hydrant-Master Universal Key

Lightweight - robust - practical

No. 3461




Order No.	Operating key for	Length	Weight	
3410	Service valves	850	1,90	
3420	Valves, extension spindles and below ground hydrants	1130	4,10	
3460	Above ground hydrants	420	1,25	

Operating key

No. 3410

No. 3420

No. 3460



Design features

- of ductile iron

Order No.	Coupling	Weight	
KR281.1	A+B+C	1,25	

Hydrant key with adapter

to open the theft indicator No. KRE300PC

No. KR281.1

