



Other sizes or ranges on request

Always use the **NOVA SIRIA** reinforcing liner inside the pipe when installing an end restraint coupling onto PE and pressure PVC pipes. Liners are manufactured from carbon steel and coated with Rilsan Nylon 11 anticorrosion coating.

The liners reinforce the section of the pipe intended for the **MULTIGRIP** improving the overall performance of the radial grip. The design of the reinforcing liner can involve the use of one or more expansion wedges according to the ovality and tolerance of the PE/PVC pipe.

During the liner installation stage, once the insertion of grub screws and nuts system is completed, the internal threaded bolts, nuts and washers, necessary to expand the liner will be removed in order to unscrew the lifting eyes.

IN THIS WAY NO INTERNAL OBSTRUCTION OF FLOW WILL BE CREATED.

NSCAN	SDR			
	7,4	11	17	26
355	258,0	290,6	312,8	327,8
400	290,6	327,4	352,6	369,4
450	327,0	368,2	396,6	415,6
500	-	409,2	440,6	461,8
560	-	458,4	493,6	517,2
630	-	515,6	555,2	581,8
710	-	581,0	625,8	655,6
800	-	654,6	705,2	738,8
900	-	736,6	793,7	831,2
1000	-	818,4	881,4	923,6
1200	-	-	-	1108,2
1400	-	-	-	1293,0
1600	-	-	-	1477,6
L	350			