

Österreichische Vereinigung für das Gas- und Wasserfach
A-1010 Wien, Schubertring 14

Telefon: +43/1/5131588-0* / Telefax: +43/1/5131588-25
E-Mail: office@ovgw.at / Internet: www.ovgw.at

Accredited by the Federal Ministry for Labour and Economy



ÖVGW Certificate

of the conferment of the right to use the ÖVGW Quality Mark for Water

| Real | stration | num | har |
|--------|----------|-------|-----|
| I VOGI | suauon | Hulli | |

W 1.363

Period of validity

until the end of May 2026

Owner

Distribution in Austria

E. Hawle Armaturenwerke GmbH

Wagrainerstraße 13 4840 Vöcklabruck

Manufacturer

E. Hawle Armaturenwerke GmbH / AT

Type of test

Renewal and supplementary test

Reason for supplement

Maximum operating pressure has been increased to 16 bar

Test report

TGM - VA HL 9119 dated 12 May 2023

Quality standards / Testing directives

- QS-W 300, Annex K.5 version January 2019
- QS-W 100 version November 2022
- QS-W 200 version May 2020

Product

Water meter installation sets

Type: 2930, DN 40

2931, DN 25, DN 32 **2932**, DN 25

2960, DN 50

Maximum operating pressure: 16 bar Maximum operating temperature: 30 °C

Components included in the scope of registration:

 Mounting bracket according to ÖNORM Standard B 2534:

| Order No. | DN | Valve connections |
|-----------|----|-----------------------------------|
| 2930 | 40 | 2 internal threads G 1/2" ISO 228 |
| 2931 | 25 | 2 internal threads G 1" ISO 228 |
| | 32 | 2 external threads R 1 ¼" |
| | | EN 10226 |
| 2932 | 25 | 1 ZAK 34 socket connection, |
| | | 1 internal thread G 1" ISO 228 |
| 2960 | 50 | 2 internal threads G 2" ISO 228 |

- · Mounting bracket made of cast iron, coated
- Shut-off valves made of brass (straight-pattern shut-off valves)
- with integrated backflow-preventer

The conferment is based on the General Terms and Conditions GW 30 ÖVGW Quality Mark for Gas & Water Products "Conditions for the award of the ÖVGW Quality Mark for gas and water supply products."