



## Product certificate K78328/04

Issued 2019-10-15

Replaces K78328/03

Page 1 of 3

### Ductile cast iron fittings for PVC-U and PE piping systems

#### STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

### Fabryka Armatury Hawle Spółka z o.o.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K773 "Ductile cast iron fittings for PVC-U and PE piping systems" dated 08-09-2014.

which covers the requirements of

**EN 12842:** "Ductile iron fittings for PVC-U or PE piping systems - Requirements and test methods"

Ronald Karel  
Kiwa

*Publication of this certificate is allowed.*

*Advice: consult [www.kiwa.nl](http://www.kiwa.nl) in order to ensure that this certificate is still valid.*

CERTIFICATE

286180711

#### Kiwa Nederland B.V.

Sir Winston Churchillaan 273  
Postbus 70  
2280 AB RIJSWIJK  
The Netherlands  
Tel. +31 88 998 44 00  
Fax +31 88 998 44 20  
info@kiwa.nl  
[www.kiwa.nl](http://www.kiwa.nl)

#### Company

Fabryka Armatury Hawle Spółka z o.o.  
Ul. Piaskowa 9  
62-028 KOZIEGLOWY  
Poland  
Tel. +48 (0) 61 8111 409  
Fax +48 (0) 61 8111 413  
info@hawle.pl  
[www.hawle.pl](http://www.hawle.pl)



Certification process  
consists of initial and  
regular assessment of:

- quality system
- product

## Ductile cast iron fittings for PVC-U and PE piping systems

---

### PRODUCT SPECIFICATION

The products mentioned below belong to this product certificate

#### System 2000

Type of fitting	Article Number	Range
Flanges	0400	DN50/63 – DN200/225
Connectors	0430	63 - 225 mm
All socket tees (MMB fittings)	8515	63 - 225 mm
Double socket tees with flanged branch (MMA fittings)	8525	63 - 225 mm
Bends 90°	8535	63 - 225 mm
Bends 45°	8545	63 - 225 mm
Bends 30°	8555	90, 110, and 160 mm
Bends 11°	8557	90 - 110 mm
End caps	8075	63 - 225 mm
Duckfoot bends	5075	DN80-100 (63 – 110 mm)

REMARK: The products listed above can be used with an allowable operating pressure (PFA) of up to and including 16 bar.

#### Fitness for contact with drinking water



This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).

These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

#### MARKING

The Kiwa®-mark products are marked with the word mark "KIWA  of 

Place of the mark:

- on the fitting.

\*) for small fittings marking with only KK is permitted

Compulsory specifications:

- manufacturer's name or logo;
- the last two digits of the production year;
- material specification;
- external diameter (in mm) range of the piping with which the coupling can be used;
- nominal pressure.

Method of marking:

- Non-erasable;
- visible after assembly.

#### APPLICATION AND USE

The products are intended to be applied in piping systems for the transport of drinking water met de nominal size of DN 40 up to and including DN 700 with a with a maximum water pressure 1 MPa and water temperature of 30 °C.

## Ductile cast iron fittings for PVC-U and PE piping systems

---

### **RECOMMENDATIONS FOR CUSTOMERS**

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Fabryka Armatury Hawle Spółka z o.o.

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.